

®
ITW CHEMTRONICS

MSDS #0908

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**Company Address:**

8125 Cobb Center Drive
Kennesaw, GA 30152

Product Information: 800-TECH-401
Customer Service: 800-645-5244

Emergency: (Chemtrec) 800-424-9300
Revision Date: February 10, 2007

Product Identification

STATIC FREE™ PLAST-N-GLAS™

Product Code: ES1668, ES1668C

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Wt. % Range
Deionized water	7732-18-5	50.0-95.0
Isopropanol	67-63-0	1.0-20.0
Propane	74-98-6	1.0-20.0
Isobutane	75-28-5	1.0-20.0
Propylene glycol n-butyl ether	5131-66-8	1.0-20.0

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Clear, colorless liquid with fresh odor. This product is not flammable. Vapors released may become flammable if allowed to accumulate. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce drowsiness and a headache.

Potential Health Effects:

Eyes: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Skin: Contact causes skin irritation.

Ingestion: Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.

Inhalation: Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

Pre-Existing Medical Conditions Aggravated by Exposure: Skin, eye.

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

Ingestion: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get immediate medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

US Flame Projection: Nonflammable

LEL/UEL: Not established (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches, which lead to waterways.

Small Spills: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.

SECTION 8: EXPOSURE CONTROLS/PERSONNEL PROTECTION**Exposure Guidelines:**

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Isopropanol	200 ppm	400 ppm	400 ppm
Propylene glycol n-butyl ether	NA	NA	NA

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	1	1
Flammability	1	1
Reactivity	0	0
Personal Protection	-	B

®

ITW CHEMTRONICS

MSDS #0908

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIESPhysical State: Opaque white foamOdor: Floral fragrancepH: 9.0-9.5 (liquid)Vapor Pressure: 19 mm Hg @ 20 CBoiling Point: 212 F (100C) (liquid only)Vapor Density: >1 @ 68F

(Air=1)

Solubility in water:> 90% by wt.Specific Gravity: 0.95 (liquid only)

(Water =1)

Evaporation Rate: >1

(Butyl acetate=1)

Viscosity: 1 (Approx.)

Percent Volatile: > 98% (Approx.)

SECTION 10: STABILITY AND REACTIVITYStability: This product is stable. Conditions to Avoid: Do not spray near open flames, red hot surfaces or other sources of ignition.Incompatibility: Do not mix strong oxidizing agents.Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.Hazardous Polymerization: Will not occurConditions to Avoid: NA**SECTION 11: TOXICOLOGICAL INFORMATION**Inhalation:

Isopropanol LD50/rats 12,000 ppm/4hrs

Ingestion:

Isopropanol LD50/rats 5,800 mg/kg

Propylene glycol n-butyl ether* LD50/rats 3,300 mg/kg

Skin:

Propylene glycol n-butyl ether LD50/rabbits 3100 mg/kg

Isopropanol Rabbit MLD

Eye:

Isopropanol RabbitSL-MOD

*Information received from manufacturer.

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none

Teratogenic effects: none

Mutagenic effects: none

SECTION 12: ECOLOGICAL INFORMATION**Environmental Impact Information**

Avoid runoff into storm sewers and ditches, which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is:

1-800-424-8802**SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATION

Proper Shipping Name	UN Number	Class	Sub. Risk	Pkg. Group	Hazard Label	Pkg. Instr.	Max. Quantity
<u>Air:</u> Aerosols nonflammable	UN 1950	2.2	NA	NA	Nonflammable Gas	203 Y203	75 k.g; 30 kg
<u>Ground:</u> Consumer Commodity ORM-D	NA	ORM-D	NA	NA	ORM-D	Pkg. Auth.	173.306

SECTION 15: REGULATORY INFORMATION**SECTION 313 SUPPLIER NOTIFICATION**

This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA).

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class A

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

This product is a Level 1 aerosol. Do not puncture or incinerate containers. Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.