

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**Company Address:**

8125 Cobb Center Drive
Kennesaw, GA 30152

Product Information: 800-TECH-401
Customer Service: 800-645-5244

Emergency: (Chemtrec) 800-424-9300
Revision Date: January 15, 2003

Product Identification**CIRCUITWORKS® CONDUCTIVE EPOXY - Part B (Hardener)**

Product Code: CW2400, CW2400BLK (Part B) (Formerly: CW2400-T)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Wt. % Range
Silver (Metallic)	7440-22-4	60.0-90.0
Modified Aliphatic Amine	140-31-8	10.0-25.0

SECTION 3: HAZARDOUS IDENTIFICATION

Emergency Overview: Silver/gray paste with amine odor. This product is nonflammable. Liquid will cause chemical burns in eye and on skin. Breathing high concentrations may cause respiratory irritation and allergic respiratory reaction.

Potential Health Effects:

Eyes: Liquid and vapors of this product may cause chemical burns in the eye. Damage is irreversible.

Skin: Contact may cause chemical burns on the skin. Sensitizer - may cause allergic skin reaction.

Ingestion: Harmful if swallowed. May cause chemical burn in gastrointestinal tract and may be potentially toxic. Silver ingestion may result in generalized argyria.

Inhalation: Harmful if inhaled. High concentrations in immediate area can cause respiratory irritation if inhaled. Sensitizer - may cause allergic respiratory reaction.

Pre-Existing Medical Conditions Aggravated by Exposure: Heart, lung, eye, skin

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with large amounts of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined by a Physician.

Skin: Remove contaminated clothing and wash skin with soap and water. Get medical attention if irritation persists. Wash clothes separately before reuse.

Ingestion: If swallowed, seek medical attention. Neutralize with milk or dilute with water.

Inhalation: In case of exposure to high concentrations of vapor or mist, remove to fresh air. If breathing is difficult, give oxygen and call a Physician. If breathing has stopped, apply artificial respiration and call a Physician.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: > 200°F (Setaflash) **LEL/UEL:** 0.9/NA (% by volume in air)

Extinguishing Media: Use carbon dioxide or dry chemicals for small fires, aqueous foam or water for large fires.

Fire Fighting Instructions: Remove all ignition sources. Closed containers may rupture due to build-up of pressure when exposed to extreme heat. As in any fire, wear self-contained breathing apparatus (pressure demand, OSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Remove all sources of ignition (sparks, open flames, etc.). Wear self-contained breathing apparatus and appropriate personal protective equipment. Ventilate area and contain and absorb spill with inert material. Collect spill by scooping up liquids and absorbent material and place in a chemical waste container for proper disposal. Do not flush to sewer. Prevent material from entering storm sewers, ditches that lead to waterways and ground.

Small Spills: Absorb spill with absorbent material, then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with skin, eyes or clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor. Do not reuse this container. Store in a cool dry place, away from heat, sparks or flames. Keep container tightly closed when not in use. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.**SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION****Exposure Guidelines:**

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Silver	0.1 mg/m3	0.01mg/m3	NA
Modified Aliphatic Amine	NA	NA	NA

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Wear safety glasses with side shields or goggles and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	3	3
Flammability	1	1
Reactivity	0	0
Personal Protection	-	B

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Silver/gray Paste

Odor: Amine

pH: NA

Vapor Pressure: <1.0 mmHg @ 20°C

Percent Volatile: < 0.5%

Vapor Density: >1

(Air = 1)

Solubility in Water: Partially Soluble

Specific Gravity: 2.5-2.8

Evaporation Rate: <1

(Butyl acetate=1)

Boiling Range: >400°F

SECTION 10: STABILITY AND REACTIVITY

Stability: This product is stable. Conditions to Avoid: Excessive Heat.

Incompatibility: Avoid epoxy resins and isocyanates, strong acids, mineral and organic acids, strong bases, caustics and alkali contamination.

Products of Decomposition: Carbon monoxide, carbon dioxide and oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Conditions to avoid: Contamination with strong acids, bases, epoxy resins or isocyanates can cause polymerization.

SECTION 11: TOXICOLOGICAL INFORMATION

Ingredients	LD50		LC50 (ppm)
	(rat) Oral	(rbt) Dermal	(rat) Inhalation
Silver (metallic)	>10000 mg/kg (mouse)	NA	NA
Modified Aliphatic Amine	2.14 gm/kg	880 µL/kg	NA

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none

Teratogenic effects: none

Mutagenic effects: none

SECTION 12: ECOLOGICAL INFORMATION**Environmental Impact Information**

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: **1-800-424-8802**

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATIONAir and Ground Shipments:

Adhesives, sealants
Not Regulated

SECTION 15: REGULATORY INFORMATION**SECTION 313 SUPPLIER NOTIFICATION**

This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.