

®
ITW CHEMTRONICS

MSDS #-0719

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**Company Address:**

8125 Cobb Center Drive
Kennesaw, GA 30152

Product Information: 800-TECH-401
Customer Service: 800-645-5244

Emergency: (Chemtrec) 800-424-9300
Revision Date: October 31, 2007

Product Identification**Chemask NA Non-Ammoniated Temporary Spot Mask**

Product Code: CNA8, CNA1

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Product Ingredient Information	CAS#	Wt. % Range
Deionized water	7732-18-5	45.0-55.0
Acrylic polymer	mixture	35.0-45.0
Polyurethane resin	proprietary	1.0-5.0
diethylene glycol dibenzoate	120-55-8	1.0-5.0
dipropylene glycol dibenzoate	27138-31-4	1.0-5.0
titanium dioxide	13463-67-7	0.1-1.0

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Viscous, opaque green liquid. This product is not flammable. Liquid may irritate eyes and skin under repeated or prolonged exposure.

Potential Health Effects:

Eyes: Liquid and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Skin: Contact causes skin irritation. Sensitizer - may cause allergic skin reaction.

Ingestion: Harmful if swallowed. Irritating to mouth, throat and stomach. May cause nausea, vomiting, and diarrhea.

Inhalation: High concentrations of vapors may cause headaches, nausea, dizziness, and respiratory irritation if inhaled.

Pre-Existing Medical Conditions Aggravated by Exposure: Lung, eye, skin

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with large amounts of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

Ingestion: If swallowed, seek medical attention immediately.

Inhalation: In case of exposure to high concentrations of vapor, remove to fresh air. If breathing is difficult, give oxygen and get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None to boiling (TCC)

LEL/UEL: NA (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert absorbant material, then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.

Small Spills: Absorb spill with absorbent material, then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor.

Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines:**

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Acrylic polymer	NA	NA	NA
Polyurethane resin	NA	NA	NA
diethylene glycol dibenzoate	NA	NA	NA
dipropylene glycol dibenzoate	NA	NA	NA

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	1	1
Flammability	0	0
Reactivity	0	0
Personal Protection	-	B

®

ITW CHEMTRONICS

MSDS #-0719

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIESPhysical State: Opaque green, viscous materialOdor: NoneVapor Pressure: NAVapor Density: NApH: 6.0-8.0Boiling Range: >212°FSolubility in Water: DispersibleSpecific Gravity: 1.22Evaporation Rate: >1

(Butyl Alcohol= 1)

Viscosity: NAPercent Volatile: <0.5**SECTION 10: STABILITY AND CHEMICAL PROPERTIES**Stability - Stable.Conditions to Avoid: Storage above 120° F, exposure to light, loss of polymerization inhibitor, contamination with incompatible materials.Incompatibility: Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents.Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide, HCN, and hydrocarbons.Hazardous Polymerization: Will not occur**SECTION 11: TOXICOLOGICAL INFORMATION**Inhalation: Not availableIngestion: Not availableSkin: Not available**Cancer Information:** No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none

Teratogenic effects: none

Mutagenic effects: none

SECTION 12: ECOLOGICAL INFORMATION**Environmental Impact Information**

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is:

1-800-424-8802**SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATIONAir: Coating Compound, Not RegulatedGround: Coating Compound, Not Regulated**SECTION 15: REGULATORY INFORMATION****SECTION 313 SUPPLIER NOTIFICATION**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

None

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All ingredients of this product are listed on the TSCA Inventory.

CALIFORNIA PROPOSITION 65: WARNING: This product contains formaldehyde, a chemical known to the state of California to cause cancer.**WHMIS:** Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

Normal ventilation for standard manufacturing practices is usually adequate.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.