

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Trade name:** **44 Flux-Cored Lead (Pb) Solder**

**Relevant identified uses of the substance or mixture and uses advised against**

Solder

Professional use of lead solder

### 1.3 Details of the supplier of the safety data sheet

This Safety Data Sheet has been updated in accordance with the Globally Harmonized System (GHS).

#### Manufacturer/Supplier:

Kester Inc.

800 West Thorndale Avenue

Itasca, IL 60143

Tel 00+1 + 630 616 4000

ITW Specialty Materials (Suzhou) Co., Ltd.

Hengqiao Road, Wujiang Economic Development Zone

Suzhou, Jiangsu Province, China 215200

Tel +86 512 82060807

**Further information obtainable from:** Product Compliance: EHS\_Kester@kester.com

#### 1.4 Emergency telephone number:

TRANSPORT EMERGENCY Phone: CHEMTREC (800) 424-9300 (Outside US & Canada): 00+1 +703 527 3887

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS07 GHS08

**Signal word** Danger

#### Hazard-determining components of labelling:

LEAD (Pb)

#### Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

(Continued on page 2)

GB

**Trade name: 44 Flux-Cored Lead (Pb) Solder**

(Continued from page 1)

H351 Suspected of causing cancer.  
 H360 May damage fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P280 Wear protective gloves / eye protection.  
 P270 Do not eat, drink or smoke when using this product.  
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P402 Store in a dry place.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Warning! Contains lead.  
 For use in industrial installations only.  
 Restricted to professional users.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

**PBT:** Not applicable.  
**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Chemical components:**

CAS: 7440-31-5 EINECS: 231-141-8	TIN (Sn)	30-65%
CAS: 7439-92-1 EINECS: 231-100-4	LEAD (Pb) ⚠ Carc. 2, H351; Repr. 1B, H360; STOT RE 2, H373 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	30-65%
	Rosin ⚠ Skin Sens. 1, H317	3.0-5.0%
CAS: 7440-22-4 EINECS: 231-131-3	SILVER (Ag)	^^
CAS: 7440-50-8 EINECS: 231-159-6	COPPER (Cu)	^^
CAS: 7440-36-0 EINECS: 231-146-5	ANTIMONY (Sb)	^^
CAS: 7440-69-9 EINECS: 231-177-4	BISMUTH (Bi)	^^

**Additional information:**

Composition and weight percent of solder alloys varies widely and can be determined by product label. <sup>^^ See Product Alloy Table</sup>  
 This solder product does not contain any Substance of Very High Concern (SVHC) on the European Chemicals Agency (ECHA) candidate list.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

**General information:** Follow general first aid procedures.

**After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.  
 Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** Seek immediate medical advice.

(Continued on page 3)

GB

**Trade name: 44 Flux-Cored Lead (Pb) Solder**

(Continued from page 2)

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**
**Suitable extinguishing agents:** CO<sub>2</sub>. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO<sub>x</sub>)
Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**
**Protective equipment:** Wear self-contained respiratory protective device.

**SECTION 6: Accidental release measures**
**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**
**7.1 Precautions for safe handling**

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:** No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities**
**Storage:**
**Requirements to be met by storerooms and receptacles:** Store in a cool location.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**
**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**
**Ingredients with limit values that require monitoring at the workplace:**
**7439-92-1 LEAD (Pb)**

 PEL Long-term value 0.05\* mg/m<sup>3</sup>

 REL Long-term value 0.05\* mg/m<sup>3</sup>

(Continued on page 4)

GB

**Trade name: 44 Flux-Cored Lead (Pb) Solder**

(Continued from page 3)

\*8-hr TWA, excl. lead arsenate; See PocketGuideApp.C

TLV Long-term value 0.05\* mg/m<sup>3</sup>

\*and inorganic compounds, as Pb; BEI

**7440-31-5 TIN (Sn)**PEL Long-term value 2 mg/m<sup>3</sup> metalREL Long-term value 2 mg/m<sup>3</sup>TLV Long-term value 2 mg/m<sup>3</sup> metal**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

**Respiratory protection:**

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

**Protection of hands:**

Protective gloves

**Material of gloves**

Nitrile rubber, NBR

Natural rubber, NR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Safety Glasses with Side Shields Required**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:** Solid**Colour:** Silver grey**Odour:** Odourless**pH-value:** Not applicable.**Change in condition****Melting point/Melting range:** 183 - 301 °C  
Undetermined.**Flash point:** Undetermined.**Flammability (solid, gaseous):** Not determined.**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product does not present an explosion hazard.**Vapour pressure:** Not applicable.**Density at 20 °C:** 8.4 - 11.1 g/cm<sup>3</sup>

(Continued on page 5)

GB

**Trade name: 44 Flux-Cored Lead (Pb) Solder**
**Vapour density** Not applicable.

(Continued from page 4)

**Solubility in / Miscibility with water:** Insoluble.

**SECTION 10: Stability and reactivity**
**10.1 Reactivity**
**10.2 Chemical stability**
**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** Strong acids, strong oxidizers.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**
**11.1 Information on toxicological effects**
**Acute toxicity**
**Primary irritant effect:**
**Skin corrosion/irritation** Irritant to skin and mucous membranes.

**Serious eye damage/irritation** Smoke during soldering can cause eye irritation.

**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

**SECTION 12: Ecological information**
**12.1 Toxicity**
**Aquatic toxicity:** No further relevant information available.

**Additional ecological information:**
**General notes:**

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.

**12.5 Results of PBT and vPvB assessment**
**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

**Uncleaned packaging:**
**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**
**14.1 UN-Number**

Not regulated

(Continued on page 6)

GB

Trade name: **44 Flux-Cored Lead (Pb) Solder**

(Continued from page 5)

<b>14.2 UN proper shipping name</b>	Not regulated
<b>IMDG, IATA</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>ADR, IMDG, IATA</b>	
<b>Class</b>	Not regulated.
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All ingredients are listed on the following Government Inventories:

China:	Inventory of Existing Chemical Substances in China (IECSC)
Korea:	Korea Existing Chemicals List (ECL)
Europe:	European Inventory of Existing Commercial Chemical Substances (EINECS)
Japan:	Inventory of Existing and New Chemical Substances (ENCS)
Philippines:	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
USA:	TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS07 GHS08

**Signal word** Danger**Hazard-determining components of labelling:**

LEAD (Pb)

**Hazard statements**

H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P280	Wear protective gloves / eye protection.
P270	Do not eat, drink or smoke when using this product.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P402	Store in a dry place.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Continued on page 7)

**Trade name: 44 Flux-Cored Lead (Pb) Solder**

(Continued from page 6)

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Safety Data Sheet (SDS) relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet (SDS) as a source for hazard information.

**Department issuing MSDS:** Product Compliance / EHS Department

**Contact:** EHS\_Kester@kester.com

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

\* **Data compared to the previous version altered.**

GB

## 44 FLUX-CORED LEAD (Pb) PRODUCT ALLOYS INCLUDED IN THIS SDS

Alloy	Flux	Diameter	Core	Description	Part #
AG03PB97	44	0.062	50	AG03PB97 #50/44 .062 5 LB SPL	2674000059
SN01PB97.5AG1.5	44	0.025	58	SN01PB97.5AG1.5 #58/44 .025 1 LB SPL	2400150017
SN40PB60	44	0.062	66	SN40PB60 #66/44 .062 1 LB SPL	2440600061
SN40PB60	44	0.093	66	SN40PB60 #66/44 .093 5 LB SPL	2640600066
SN40PB60	44	0.093	66	SN40PB60 #66/44 .093 1 LB SPL	2440600066
SN40PB60	44	0.25	66	SN40PB60 #66/44 .250 EZD	2940600177
SN50PB50	44	0.062	66	SN50PB50 #66/44 .062 5 LB SPL	2650500061
SN50PB50	44	0.062	66	SN50PB50 #66/44 .062 1 LB SPL	2450500061
SN50PB50	44	0.093	66	SN50PB50 #66/44 .093 1 LB SPL	2450500066
SN50PB50	44	0.125	58	SN50PB50 #58/44 .125 1 LB SPL	2450500068
SN50PB50	44	0.125	66	SN50PB50 #66/44 .125 1 LB SPL	2450500069
SN5PB93.5AG1.5	44	0.01	58	SN05PB93.5AG1.5 #58/44 .010 1 LB SPL	2473400000
SN5PB93.5AG1.5	44	0.015	58	SN05PB93.5AG1.5 #58/44 .015 1 LB SPL	2473400006
SN5PB93.5AG1.5	44	0.031	58	SN05PB93.5AG01.5 #58/44 .031 1 LB SPL	2473400026
SN5PB93.5AG1.5	44	0.062	58	SN05PB93.5AG01.5 #58/44 .062 1 LB SPL	2473400060
SN60PB40	44	0.015	66	SN60PB40 #66/44 .015 1 LB SPL	2460400007
SN60PB40	44	0.02	66	SN60PB40 #66/44 .020 1 LB SPL	2460400010
SN60PB40	44	0.025	58	SN60PB40 #58/44 .025 1 LB SPL	2460400017
SN60PB40	44	0.025	66	SN60PB40 #66/44 .025 1 LB SPL	2460400018
SN60PB40	44	0.031	58	SN60PB40 #58/44 .031 1 LB SPL	2460400026
SN60PB40	44	0.031	66	SN60PB40 #66/44 .031 1 LB SPL	2460400027
SN60PB40	44	0.04	58	SN60PB40 #58/44 .040 1 LB SPL	2460400038
SN60PB40	44	0.04	58	SN60PB40 #58/44 .040 5 LB SPL	2660400038
SN60PB40	44	0.04	66	SN60PB40 #66/44 .040 5 LB SPL	2660400039
SN60PB40	44	0.04	66	SN60PB40 #66/44 .040 1 LB SPL	2460400039
SN60PB40	44	0.05	58	SN60PB40 #58/44 .050 1 LB SPL	2460400052
SN60PB40	44	0.05	66	SN60PB40 #66/44 .050 20 LB SPL	2860400053
SN60PB40	44	0.05	66	SN60PB40 #66/44 .050 1 LB SPL	2460400053
SN60PB40	44	0.062	58	SN60PB40 #58/44 .062 1 LB SPL	2460400060
SN60PB40	44	0.062	66	SN60PB40 #66/44 .062 20 LB SPL	2860400061
SN60PB40	44	0.062	66	SN60PB40 #66/44 .062 5 LB SPL	2660400061
SN60PB40	44	0.062	66	SN60PB40 #66/44 .062 1 LB SPL	2460400061
SN60PB40	44	0.081	66	SN60PB40 #66/44 .081 5 LB SPL	2660400103
SN60PB40	44	0.093	66	SN60PB40 #66/44 .093 1 LB SPL	2460400066
SN60PB40	44	0.125	58	SN60PB40 #58/44 .125 5 LB SPL	2660400068
SN60PB40	44	0.125	66	SN60PB40 #66/44 .125 5 LB SPL	2660400069
SN60PB40	44	0.125	66	SN60PB40 #66/44 .125 1 LB SPL	2460400069
SN62PB36AG2	44	0.02	58	SN62PB36AG02 #58/44 .020 1 LB SPL	2471500009
SN62PB36AG2	44	0.02	66	SN62PB36AG02 #66/44 .020 1 LB SPL	2471500010
SN62PB36AG2	44	0.025	66	SN62PB36AG02 #66/44 .025 1 LB SPL	2471500018
SN62PB36AG2	44	0.031	66	SN62PB36AG02 #66/44 .031 1 LB SPL	2471500027
SN62PB36AG2	44	0.05	66	SN62PB36AG02 #66/44 .050 1 LB SPL	2471500053
SN62PB36AG2	44	0.062	58	SN62PB36AG02 #58/44 .062 5 LB SPL	2671500060
SN63PB36.65SB.35	44	0.02	66	SN63PB36.65SB.35 #66/44 .020 1 LB SPL	2400630010
SN63PB37	44	0.01	66	SN63PB37 #66/44 .010 1 LB SPL	2463370001
SN63PB37	44	0.015	66	SN63PB37 #66/44 .015 1 LB SPL	2463370007
SN63PB37	44	0.02	58	SN63PB37 #58/44 .020 1 LB SPL	2463370009
SN63PB37	44	0.02	66	SN63PB37 #66/44 .020 1 LB SPL	2463370010
SN63PB37	44	0.025	58	SN63PB37 #58/44 .025 1 LB SPL	2463370017
SN63PB37	44	0.025	66	SN63PB37 #66/44 .025 1 LB SPL	2463370018
SN63PB37	44	0.031	58	SN63PB37 #58/44 .031 1 LB SPL	2463370026
SN63PB37	44	0.031	66	SN63PB37 #66/44 .031 1 LB SPL	2463370027
SN63PB37	44	0.04	58	SN63PB37 #58/44 .040 5 LB SPL	2663370038
SN63PB37	44	0.04	66	SN63PB37 #66/44 .040 1 LB SPL	2463370039
SN63PB37	44	0.05	66	SN63PB37 #66/44 .050 1 LB SPL	2463370053
SN63PB37	44	0.062	58	SN63PB37 #58/44 .062 1 LB SPL	2463370060
SN63PB37	44	0.062	66	SN63PB37 #66/44 .062 1 LB SPL	2463370061
SN63PB37	44	0.125	66	SN63PB37 #66/44 .125 1 LB SPL	2463370069
SN95SB5	44	0.031	66	SN95SB05 #66/44 .031 1 LB SPL	2400010027