

SAFETY DATA SHEET

CH775_CH797_ I.P.A. SOLVENT

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name CH775_CH797_ I.P.A. SOLVENT

Product number 758CH775, 758CH797

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Manufacturer Techni-Tool, Inc.
1547 North Trooper Road
Worcester, PA 19490-1117
610-941-2400
610-940-5485
www.techni-tool.com

Emergency telephone number

Emergency telephone CHEMTREC (800) 424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2A - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Physicochemical The product is highly flammable. Vapors may form explosive mixtures with air.

Label elements

Pictogram



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

CH775_CH797_ I.P.A. SOLVENT

Precautionary statements	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P240 Ground/ bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing vapor/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Supplemental label information Safety data sheet available on request. For use in industrial installations only.

Contains PROPAN-2-OL

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients**Mixtures**

PROPAN-2-OL	60-100%
CAS number: 67-63-0	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition comments TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200

Composition**4. First-aid measures****Description of first aid measures**

General information The product is flammable. CAUTION! First aid personnel must be aware of own risk during rescue! Move affected person to fresh air at once. Place unconscious person on the side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.

CH775_CH797_ I.P.A. SOLVENT

Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Consult a physician for specific advice.
Skin Contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause drowsiness and dizziness. Headache. Irritation of nose, throat and airway.
Ingestion	Ingestion of large amounts may cause unconsciousness. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May cause skin irritation/eczema.
Eye contact	May cause temporary eye irritation. Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Heating may generate flammable vapors. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon.
<u>Advice for firefighters</u>	
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapors.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

CH775_CH797_ I.P.A. SOLVENT

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Warn everybody of potential hazards and evacuate if necessary. If leakage cannot be stopped, evacuate area. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards.

7. Handling and storage

Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Storage tanks and other containers must be grounded. Static electricity and formation of sparks must be prevented. Ground and bond containers when transferring material.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container. Keep container dry. Ground container and transfer equipment to eliminate sparks from static electricity. Do not store near heat sources or expose to high temperatures.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Cleaning agent.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Additional Occupational Exposure Limits

Ingredient comments WEL = Workplace Exposure Limits

CH775_CH797_ I.P.A. SOLVENT

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Not considered to be a significant hazard due to the small quantities used. Wear apron or protective clothing in case of contact.

Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Clear liquid.
Color	Colorless.
Odor	Characteristic. Alcoholic.
Odor threshold	22 ppm
pH	6.5 - 7.2
Melting point	Not relevant.
Initial boiling point and range	82 - 83°C/179 - 182°F @ 101.3 kPa
Flash point	12°C/54°F TCC (Tag closed cup).
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 12.0 Lower flammable/explosive limit: 2.0
Other flammability	No information available.
Vapor pressure	41 hPa @ 20°C
Vapor density	1.82

CH775_CH797_ I.P.A. SOLVENT

Relative density	0.785 g/cm ³ @ 20°C
Bulk density	No information available.
Solubility(ies)	Completely soluble in water.
Partition coefficient	Pow: 0.05
Auto-ignition temperature	399°C/750°F
Viscosity	2.43 mPa s @ 20°C
Refractive index	No information available.
Particle size	Not applicable.
Molecular weight	No information available.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 785 g/litre.

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidizing agents. Strong alkalis. Strong mineral acids.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Fire creates: Vapors/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information**Information on toxicological effects**

Other health effects	There is no evidence that the product can cause cancer.
Inhalation	May cause respiratory system irritation. Vapors may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Substance may be harmful if swallowed. May cause nausea, headache, dizziness and intoxication. May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhea.
Skin Contact	Product has a defatting effect on skin. May cause skin irritation/eczema.
Eye contact	Irritating to eyes. Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

CH775_CH797_ I.P.A. SOLVENT

Acute and chronic health hazards Keep out of the reach of children.

Toxicological information on ingredients.**PROPAN-2-OL****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 13,000.0

Species Rabbit

ATE dermal (mg/kg) 13,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 16,000.0

Species Rat

ATE inhalation (vapours mg/l) 16,000.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Toxicity**Ecological information on ingredients.****PROPAN-2-OL**

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The product is readily biodegradable.

Bioaccumulative potential

CH775_CH797_ I.P.A. SOLVENT

Bio-Accumulative Potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Pow: 0.05

Mobility in soil

Mobility The product is soluble in water.

Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

13. Disposal considerations**Waste treatment methods**

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste is suitable for incineration. When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

General As supplied, this product is consigned under the Limited Quantities provisions.

Road transport notes Exception Applies: LIQUID CLEANING COMPOUND N.O.S. NOT D.O.T REGULATED PER 49 CFR 173.150 (b)

UN Number

UN No. (TDG) LIMITED QUANTITY

UN No. (IMDG) UN1219

UN No. (ICAO) UN1219

UN No. (DOT) LIMITED QUANTITY

UN proper shipping name

Proper shipping name (TDG) ISOPROPANOL

Proper shipping name (IMDG) ISOPROPANOL

Proper shipping name (ICAO) ISOPROPANOL

Transport hazard class(es)

TDG class 3

IMDG Class 3

ICAO class/division 3

Transport labels

CH775_CH797_ I.P.A. SOLVENT**Packing group**

TDG Packing Group	II
IMDG packing group	II
ICAO packing group	II
DOT packing group	II

Environmental hazards**Environmentally Hazardous Substance**

No.

Special precautions for user**EmS** F-E, S-D**Transport in bulk according to** Not relevant. No information required.**Annex II of MARPOL 73/78
and the IBC Code****15. Regulatory information****International Regulations****US Federal Regulations****SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard CategoriesAcute
Chronic
Fire**OSHA Highly Hazardous Chemicals**

Not listed.

US State Regulations**California Proposition 65 Carcinogens and Reproductive Toxins**

Not listed.

California Air Toxics "Hot Spots" (A-I)*PROPAN-2-OL*

Present.

CH775_CH797_ I.P.A. SOLVENT**California Air Toxics "Hot Spots" (A-II)**

Not listed.

California Directors List of Hazardous Substances*PROPAN-2-OL*

Present.

Massachusetts "Right To Know" List*PROPAN-2-OL*

Present.

Rhode Island "Right To Know" List*PROPAN-2-OL*

Present.

Minnesota "Right To Know" List*PROPAN-2-OL*

Present.

New Jersey "Right To Know" List*PROPAN-2-OL*

Present.

Pennsylvania "Right To Know" List*PROPAN-2-OL*

Present.

Inventories**Canada - DSL/NDSL**

Yes

US - TSCA

All the ingredients are listed.

16. Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	8/5/2016
Revision	14
Supersedes date	7/18/2016
SDS No.	BULK - CH775_CH797_ IPA
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
NFPA - health hazard	Irritation, minor residual injury. (1)
NFPA - flammability hazard	Ignites easily. (3)

CH775_CH797_ I.P.A. SOLVENT

NFPA - instability hazard	Normally stable. (0)
NFPA - special hazard	N/A
ACA HMIS Health rating.	Slight Hazard. (1)
ACA HMIS Flammability rating.	Ignites easily. (3)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	A

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.