

**Revision Date:** 09/24/2008

**Issue date:** 09/24/2008

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b> 5045 NTRL CR ALK RTV 3OZ TB/BN <b>Product type:</b> Silicone Sealant <b>Company address:</b> Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067	<b>Item No. :</b> 40409 / IDH No. 735892 <b>Region:</b> United States <b>Contact Information:</b> Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.loctite.com
---	--

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Substituted poly(dimethylsiloxane) Proprietary	60-100	None	None	None
Filler Proprietary	10-30	10mg/m <sup>3</sup> Inhalable fraction, 3mg/m <sup>3</sup> Respirable fraction, TWA	5mg/m <sup>3</sup> Respirable dust, 15mg/m <sup>3</sup> Total dust	None
Alkoxy silane Proprietary	5-10	None	None	None

Exposure to moisture during cure will release up to 3% ethanol Exposure to moisture during cure will release 1-2% methyl alcohol.

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

<b>Physical state:</b> Paste Product is a solid by ASTM D4359-90 <b>Color:</b> Translucent <b>Odor:</b> Slight, Alcoholic	<b>HMIS:</b> <b>HEALTH:</b> 1* <b>FLAMMABILITY:</b> 1 <b>PHYSICAL HAZARD:</b> 0 <b>Personal Protection:</b> See Section 8
---	---

**WARNING:** MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
 REPEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC SKIN REACTION.

**Relevant routes of exposure:** Skin contact, Eye contact, Inhalation

#### Potential Health Effects

**Inhalation:** Inhalation of vapors from uncured sealant may cause respiratory tract irritation. Overexposure to methanol formed during cure may cause drowsiness, nausea, and vomiting. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.

**Skin contact:** Prolonged or repeated contact with uncured sealant may cause skin irritation. Repeated or prolonged skin contact may result in allergic sensitization.

**Eye contact:** Contact with uncured product may irritate the eyes.

**Ingestion:** Not expected under normal conditions of use. May be harmful if swallowed.

**Existing conditions aggravated by exposure:** None known

**See Section 11 for additional toxicological information.**

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.
<b>Eye contact:</b>	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Ingestion:</b>	Prevent vomiting if possible. Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Product is a solid. Not classified as a flammable solid per DOT Classification Guidelines Part 173 Appendix H 7/10/2002.
<b>Autoignition temperature:</b>	Not applicable
<b>Flammable/Explosive limits-lower %:</b>	Not applicable
<b>Flammable/Explosive limits-upper %:</b>	Not applicable
<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special fire fighting procedures:</b>	Prevent inhalation of fumes and gases.
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling.
<b>Storage:</b>	Store in a dry area below 90° F
<b>Incompatible products:</b>	Keep away from strong oxidizing agents, strong Lewis or mineral acids. Avoid contact with water. Avoid exposure to light

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Provide local ventilation for prolonged use in a confined area.
<b>Respiratory protection:</b>	Use a NIOSH approved air purifying respirator with an organic vapor cartridge if the potential to exceed established exposure limits exists.
<b>Skin protection:</b>	Use impermeable gloves and protective clothing as necessary to prevent skin contact.
<b>Eye/face protection:</b>	Chemical splash goggles or safety glasses with side shields.

**See Section 2 for exposure limits.**

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste Product is a solid by ASTM D4359-90
<b>Color:</b>	Translucent
<b>Odor:</b>	Slight, Alcoholic
<b>Vapor pressure:</b>	Less than 10 mm Hg at 21.1 °C (70°F)
<b>pH:</b>	Not applicable
<b>Boiling point/range:</b>	Not applicable
<b>Melting point/range:</b>	Not available
<b>Specific gravity:</b>	1.1 at 20 deg. C
<b>Vapor density:</b>	Not available
<b>Evaporation rate:</b>	Not available
<b>Solubility in water:</b>	Polymerizes in presence of water
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	3.64%; 40.0 grams/liter

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable.
<b>Hazardous polymerization:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde. Methanol is liberated slowly upon exposure to moisture. Ethanol in case of hydrolysis.
<b>Incompatibility:</b>	Acids. Bases. Oxidizing agents. Moisture.
<b>Conditions to avoid:</b>	Exposure to moisture.

## 11. TOXICOLOGICAL INFORMATION

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Substituted poly(dimethylsiloxane) Proprietary	No	No	No
Filler Proprietary	No	No	No
Alkoxy silane Proprietary	No	No	No

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Substituted poly(dimethylsiloxane) Proprietary	No data
Filler Proprietary	Irritant
Alkoxy silane Proprietary	Irritant, Allergen

## 12. ECOLOGICAL INFORMATION

<b>Ecological information:</b>	No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.
--------------------------------	--

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

**U.S. Department of Transportation Ground (49 CFR):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**International Air Transportation (ICAO/IATA):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG):**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None  
**Exceptions:** None  
**Marine pollutant:** None

### 15. REGULATORY INFORMATION

**United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None.

**CERCLA/SARA Section 302 EHS:** None above reporting de minimus.  
**CERCLA/SARA Section 311/312:** Immediate Health Hazard, Delayed Health Hazard  
**CERCLA/SARA 313:** None above reporting de minimus.

**California Proposition 65:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**Canada Regulatory Information**

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances list.  
**WHMIS hazard class:** D.2.B

### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2,3,8,15

**Prepared by:** Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.